

## INNOVAC 500-600 BARREL WASHER

The INNOVAC BARREL WASHER for 500/600 liter barrels is designed to facilitate the cleaning and sanitizing process, significantly reducing the operator's physical effort thanks to a system that allows the barrel to be turned with ease. This portable unit is equipped with a multidirectional rotating washing system that allows a high-pressure jet of hot or cold water to reach every point inside the barrel in a 90-second rotation, ensuring optimal and safe cleaning.



### Standard equipment:

- ✓ It includes a minimum voltage safety coil in case of an electrical voltage drop.
- ✓ All sensitive parts of the machine (motor, reducer, etc.) are protected from water.
- ✓ Its design ensures a long lifespan and is entirely constructed of stainless steel, making it easy to maintain and clean.
- ✓ Prepared for 500/600 lt barrels.
- ✓ It accepts hot water up to 90°C.
- ✓ The equipment includes as standard the guide trolley that allows and facilitates the loading, unloading and rotation of the 500/600 lt barrels, saving physical effort and working time.

\* NOTE: The pressurized water and/or steam machine is not included in the standard equipment.

Power (HP)	Dimensions* (LxWxW)	Empty weight (kg)	Three-phase voltage (v)	Material	Minimum Wash Time	Maximum Water Temp. (°C)	Impact Pressure (bar)	Required Flow Rate (l/m)
0.25	1970 x 1530 x 680	56	240/400V 50 Hz	Stainless steel AISI 304	90"	60-90	80-200	15

## INNOVAC 225-500 BARREL WASHER

The INNOVAC BARREL WASHER for 225/500-liter barrels is designed to facilitate the cleaning and sanitizing process, significantly reducing the operator's physical effort thanks to a system that allows the barrel to be turned with ease. This portable unit is equipped with a multidirectional rotating washing system that allows a high-pressure jet of hot or cold water to reach every point inside the barrel in a 90-second rotation, ensuring optimal and safe cleaning.



### Standard equipment:

- ✓ It includes a minimum voltage safety coil in case of an electrical voltage drop.
- ✓ All sensitive parts of the machine (motor, reducer, etc.) are protected from water.
- ✓ Its design ensures a long lifespan and is entirely constructed of stainless steel, making it easy to maintain and clean.
- ✓ Prepared for 225/500 lt barrels.
- ✓ It accepts hot water up to 90°C.
- ✓ The equipment includes as standard the guide trolley that allows and facilitates the loading, unloading and rotation of the 225/500 lt barrels, saving physical effort and working time.

\* NOTE: The pressurized water and/or steam machine is not included in the standard equipment.

Power (HP)	Dimensions* (LxWxW)	Empty weight (kg)	Three-phase voltage (V)	Material	Minimum Wash Time	Maximum Water Temp. (°C)	Impact Pressure (bar)	Required Flow Rate (l/m)
0.25	1970 x 1530 x 680	63.5	240/400V 50 Hz	Stainless steel AISI 304	90"	60-90	80-200	15

## INNOVAC 225-300 BARREL WASHER

The INNOVAC BARREL WASHER for 225/300-liter barrels is designed to facilitate the cleaning and sanitizing process, significantly reducing the operator's physical effort thanks to a system that allows the barrel to be turned with ease. This portable unit is equipped with a multidirectional rotating washing system that allows a high-pressure jet of hot or cold water to reach every point inside the barrel in a 90-second rotation, ensuring optimal and safe cleaning.



### Standard equipment:

- ✓ It includes a minimum voltage safety coil in case of an electrical voltage drop.
- ✓ All sensitive parts of the machine (motor, reducer, etc.) are protected from water.
- ✓ Its design ensures a long lifespan and is entirely constructed of stainless steel, making it easy to maintain and clean.
- ✓ Prepared for 225/300 lt barrels.
- ✓ It accepts hot water up to 90°C.
- ✓ The equipment includes as standard the guide trolley that allows and facilitates the loading, unloading and rotation of the 225/300 lt barrels, saving physical effort and working time.

\* NOTE: The pressurized water and/or steam machine is not included in the standard equipment.

Power (HP)	Dimensions* (LxWxW)	Empty weight (kg)	Three-phase voltage (v)	Material	Minimum Wash Time	Maximum Water Temp. (°C)	Impact Pressure (bar)	Required Flow Rate (l/m)
0.25	1970 x 1530 x 680	56	240/400V 50 Hz	Stainless steel AISI 304	90"	60-90	80-200	15